


# IPC-K22

## 2MP IR Network Camera



- 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
- Outputs max. 2MP (1920 × 1080) @25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Max. IR distance: 10 m
- Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- H.264/H.265, flexible coding, applicable to various bandwidth and storage environments.
- Alarm: 1 in, 1 out; 256 G SD card, built-in Mic and speaker
- Supports 256 G Micro SD card
- 12V DC power supply, easy for installation
- Supports PIR
- Supports Wi-Fi



### Series Overview

With features of simple installation, easy operation, and high performance-cost ratio, Dahua Entry series network camera is applicable to small and medium-sized scenes, such as homes/residences, small-sized retail stores, and other small and medium-sized enterprises.

### Functions

#### Smart H.265+ & Smart H.264+

With advanced scene-adaptive rate control algorithm, Dahua smart encoding technology realizes the higher encoding efficiency than H.265 and H.264, provides high-quality video, and reduces the cost of storage and transmission.

#### Smart Illumination

Dahua Smart Illumination technology can display image in the environment of low illuminance or completely dark environment. According to the distance of the targets, the camera adjusts illuminations intensity automatically to display the details of the moving target.

#### Motion Detection

When moving objects appear in the monitoring image, Dahua Motion Detection (General) technology triggers alarm or records.

#### Day/Night

Dahua Day/Night function provides color image when illumination is adequate; when illuminance is inadequate, it switches night mode and provides white and black image. It can guarantee that the network camera can work normally when illuminance changes.

#### Voice Call

With built-in high-sensitivity Mic and high-power speaker, the camera can realize voice call through DMSS client.

Technical Specification				
Camera				
Image Sensor	1/2.7"2Megapixel progressive CMOS			
Max. Resolution	1920 (H) × 1080 (V)			
ROM	128 MB			
RAM	128 MB			
Scanning System	Progressive			
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100,000 s			
Min. Illumination	Manual 1/30 s 0.215 Lux @F2.0 (Color, 80 IRE); 0.232 Lux @F2.0 (W/B, 80 IRE); 0 Lux (IR on) Manual 1/3 s 0.0324 Lux @F2.0 (Color, 80 IRE); 0.0334 Lux @F2.0 (W/B, 80 IRE); 0 Lux (IR on)			
S/N Ratio	> 50.6 dB			
Illumination Distance	10 m (32.8 ft) (IR LED)			
Illuminator On/Off Control	Auto			
Illuminator Number	1 (IR LED)			
Pan/Tilt/Rotation Range	Pan: 0°–360° Tilt: 0°–90°			
Lens				
Lens Type	Fixed-focal			
Mount Type	M12			
Focal Length	2.8 mm			
Max. Aperture	F2.0			
Field of View	Horizontal: 102° Vertical: 54° Diagonal: 120°			
Iris Type	Fixed			
Close Focus Distance	0.5 m (1.6 ft)			
DORI Distance	Detect	Observe	Recognize	Identify
	38.6 m (126.6 ft)	15.4 m (50.5 ft)	7.7 m (25.3 ft)	3.9 m (12.8 ft)
Video				
Video Compression	H.265; H.264; H.264H; H.264B; MJPEG			
Smart Codec	H.264: Yes H.265: Yes			
Video Frame Rate	50 Hz Main stream (1920 × 1080 @25 fps), sub stream (640 × 480 @25 fps) Main stream (1280 × 960 @25 fps), sub stream (640 × 360 @25 fps) Main stream (1280 × 720 @25 fps), sub stream (320 × 240 @25 fps)			
	60 Hz Main stream (1920 × 1080 @30 fps), sub stream (640 × 480 @30 fps) Main stream (1280 × 960 @30 fps), sub stream (640 × 360 @30 fps) Main stream (1280 × 720 @30 fps), sub stream (320 × 240 @30 fps)			
	720p (1280 × 720 @30 fps), sub stream (640 × 360 @30 fps)			
	1080p (1920 × 1080 @30 fps), sub stream (640 × 360 @30 fps)			
Stream Capability	2 streams			
Resolution	1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); VGA (640 × 480); QVGA (320 × 240)			

Bit Rate Control	CBR/VBR
Video Bit Rate	H.264: 184 kbps–6144 kbps H.265: 73 kbps–6144 kbps
Day/Night	Auto (ICR)/Color/B/W
BLC	Yes
HLC	Yes
WDR	DWDR
White Balance	Auto/natural/street lamp/outdoor/manual/regional custom
Gain Control	Auto/Manual
Noise Reduction	3D DNR
Motion Detection	OFF/ON (4 areas, rectangular)
Region of Interest (RoI)	Yes (4 areas)
Smart Illumination	Yes
Image Rotation	0°/90°/180°/270°
Mirror	Yes
Privacy Masking	4 areas
Audio	
Built-in MIC	Yes
Audio Compression	G.711a; G.711Mu
Alarm	
Alarm Event	No SD card; SD card full; SD card error; network disconnection; IP conflict; illegal access; voltage detection; motion detection; video tampering
Network	
Network	RJ-45 (10/100 Base-T)
Wi-Fi	Yes
SDK and API	Yes
Protocol	HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; IPv4/v6; QoS; NTP
Interoperability	ONVIF (Profile T/Profile S/Profile G); CGI; DMSS
User/Host	20 (Total bandwidth: 50 M)
Storage	NAS; FTP; SFTP; Micro SD card (256 G)
Browser	IE: IE7 and later Chrome: Chrome 45 and later Firefox: FireFox 46 and later Safari: Mac os Safari12
Management Software	DMSS
Mobile Phone	IOS; Android
Certification	
Certification	CE-LVD: EN62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU CE-RED: Radio Equipment Directive 2014/53/EU FCC: 47 CFR FCC Part 15, Subpart B FCC ID: FCC PART 15C

Port

Alarm Input	1 channel in: 5mA 3V–5V DC
Alarm Output	1 channel out: 300mA 12V DC

Power

Power Supply	12V DC
Power Consumption	Max 2.9W (12V DC) (IR full intensity)

Environment

Operating Conditions	-10°C to +45°C (14°F to +113°F)/Less than 95%RH
Storage Conditions	-40°C to +60°C (-40°F to +140°F)

Structure

Casing	Plastic
Dimensions	Φ78.5 mm × 90.5 mm × 127.8 mm (3.1" × 3.6" × 5.0") (L × W × H)
Net Weight	160 g (0.4 lb)
Gross Weight	360 g (0.8 lb)

Ordering Information

Type	Model	Description
2MP Camera	DH-IPC-K22P	2MP IR Network Camera, PAL
	DH-IPC-K22N	2MP IR Network Camera, NTSC

Dimensions (mm[inch])

